



Sealing for a safer and greener tomorrow



Certified to NSF/ANSI/CAN 61

## STYLE 2261 SAN

# NSF-61 Braided Packing, Pure PTFE Yarn, also FDA Compliant

### Application:

#### Drinking Water Service:

Style 2261 SAN is suitable for service with a wide variety of aggressive media, but is specifically formulated to allow compliance for drinking water system components with NSF-61, from source to tap. Certification to NSF-61 provides assurance to a highest level that Style 2261SAN is safe for use in drinking water service.

#### General Service:

The packing Style 2261 SAN offers excellent performance, especially in segments of equipment for drinking water, pulp and paper, food, chemical, pharmaceutical and sugar and alcohol.

### Construction:

Style 2261 SAN is a firm, pliable interlock braided packing manufactured from the purest ePTFE filaments. Style 2261 SAN is manufactured by an advanced method of braiding and construction from the purest ePTFE filaments.

Packing Style 2261 SAN also has proprietary food grade lubricant that provide faster break-in and reduced shaft wear. Packing Style 2261 SAN complies with the F.D.A. and U.S.D.A. requirements under Title 21 Food and Drugs:

Part 177.1500 - Compliance for resins in yarn manufacturing

Part 178.3570 - Compliance for lubricant

Due to the technological edge of its filament that contains special additive encapsulated by pure PTFE, and his constructive feature offers excellent heat dissipation, which is usually generated by the sealing system. The result is its excellent sealability, particularly when compared with PTFE packings found in international markets.

### SERVICE LIMITS:

Temperature Limits		Pressure Limits	
Minimum	-450°F (-268°C)	Static	-
Maximum	536°F (280°C)	Rotating	290 psi (20 bar)
		Reciprocating	435 psi (30 bar)
Shaft Speed	3920 fpm (20 m/s)	pH	0-14



### APPROXIMATE STANDARD PACKAGE (±10%):

Size	Ft/Lb	79.6	21	16.3	10.6	7.6	5.6	4.1	3.3	2.7	1.9	1.5	1.2
	Inch	1/8	3/16	1/4	5/16	3/8	7/16	1/2	9/16	5/8	3/4	7/8	1
Standard Package (±10%)		1 Lb (0.5 Kg)	2 Lbs (1 Kg)	5 Lbs (2 Kg)		10 Lbs (5 Kg)							

Properties and application parameters shown throughout this data sheet are typical. Your specific application should not be undertaken without independent study and evaluation for suitability. For specific application recommendations consult TEADIT. Failure to select proper sealing products could result in property damage and/or serious personal injury. Specifications are subject to change without notice; this edition cancels all previous issues.

### Teadit North America.

10545 Red Bluff Rd - Pasadena - TX - 77507

Phone: 281-476-3900 - Fax: 281-476-3999 - e-mail: sales@teadit.com - engineering@teadit.com - [www.teadit.com](http://www.teadit.com)